

XANTÉ® CL30 Specifications

Engine Print Speed	Up to 30 ppm color / 37 ppm monochrome
Resolutions	1200 x 1200 dpi
Processor	PowerPC 600 MHz Processor
Memory	
XANTÉ CL30	Standard 256 MB SODIMM; (expandable to 1,024 MB max)
XANTÉ CL30D	Standard 320 MB SODIMM; (expandable to 1,024 MB max)
XANTÉ CL30HC	Standard 320 MB SODIMM; (expandable to 1,024 MB max) IDE drive standard on XANTÉ CL30D and HC models only.
Toner	
Monocomponent cartridges	Black, Cyan, Magenta, Yellow
Standard Life Cartridges	CMYK - Up to 7,500 Sheets, (letter/A4; 5% coverage)
Extended Life Cartridges	Black - Up to 15,000 sheets, (A4/letter; 5% coverage) Color - Up to 15,000 sheets, (A4/letter; 5% coverage)
Image Drum Life	*Approx. 39,000 (letter) continuous printing
Media Handling	
Main Tray	A3; Letter; A4; ledger; Executive; B4; B5; COM 10; DL; 304mm x 457mm (12" x 18")
Multipurpose Tray	327mm x 1220mm (12.9" x 47.24")*
Print Area	5mm (.197") from all edges (excluding oversize pages)
Media Weights	
Main Tray	75 g/m ² to 177 g/m ² bond; Thick stock duplex: up to 105 g/m ² .
Multipurpose Tray	Thick stock simplex: 74 g/m ² bond to 199 g/m ² index
Media Types	Plain paper, transparencies, laser-quality labels, thick paper stock. Duplexing limited to plain paper and thick stock only.
Standard Input	550 sheet standard cassette; 100 A3/letter-size in multipurpose tray; 1,650 sheet high capacity feeder (standard on XANTÉ CL30HC only)
Optional Input	Two 550 sheet paper feeders, 1,650 sheet high capacity feeder
Standard Output	500 sheets face-down, 100 sheets face up
Duplexing	Optional on XANTÉ CL30 Standard on XANTÉ CL30D and HC models
Dimensions	(W) 665mm (26.2") (D) 589mm (23.2") (H) 462mm (18.2")
Weight	70.0 kg (155 lbs) printer weight
Power Requirements	220-240 V, 50 Hz, 6A (100-120 V, 50/60 Hz, 11 A)
Noise Level	Printing - less than 54 dB; Standby - less than 45 dB
Printer Languages	True Adobe® PostScript® 3™; PCL® 5C
Typefaces	136 resident PostScript Typefaces; TrueType 42 font rasterizer; Types 1, 3, 4, 5, and 6 PostScript download font support
Standard Interfaces	Simultaneously active - 10/100 BaseT Ethernet®, IEEE-1284 bi-directional parallel, and USB**

All specs subject to change without notice.

* 26,000 (letter w/ 5% toner coverage) 3 page jobs

** 13,000 (letter w/ 5% toner coverage) 1 page job

** USB v 1.1 (on Mac, requires OS 9.x or higher)

Rev.01/09/03

FEATURES

XANTÉ CL30

Automatic Color Recalibration - The CL30 automatically recalibrates its settings after every 500 prints, maintaining high quality even after thousands of prints.

Digital Color Printing - Single-pass color utilizes four in-line digital printheads and image drums to speed the page through, laying down cyan, magenta, yellow and black toner in one pass. This technology enables faster document throughput.

Job Management Tools - Features make the CL30 one of the most versatile printing solutions in the XANTÉ arsenal.

- Print Spooling allows the host computer to continue processing jobs independent of the printer's status. Job Storage allows print jobs to be prepared and stored on the hard disk for printing on demand.
- Proof and Print allows printing of a single copy of a document for checking before printing multiple copies of the same document.
- Secure Printing allows the printing of confidential documents on printers that are shared with other users.

Media Flexibility allows for oversize printing up to 12.9" x 47.24"† (327mm x 1220mm). Print on ordinary bond paper or specialty stocks including coated, card, transparencies, and laser quality labels.

True Adobe PostScript 3 offers reliability, increased performance, and the assurance of compatibility to work from virtually any software application and hardware environment.

XANTÉ's ColourMatch Software controls colors beyond the standard settings.

XANTÉ's ColourMatch Software easily allows the user to modify colors on the XANTÉ CL30 to more closely match the color generated on the final output device. In addition, compensation can be made for different color paper stocks. For each device you select, the wizard-like software will create profiles sequentially for monitors, scanners, and the XANTÉ CL30.

XANTÉ CL30D

All of the same features as the XANTÉ CL30, plus:

- Duplex unit
- 10 GB internal hard drive
- 320 MB RAM

XANTÉ CL 30HC

All of the same features as the XANTÉ CL30D, plus:

- High capacity Tray (three 550 sheet trays)

XANTÉ CL30HCF

All of the same features as the CL30HC, plus:

- Printer stand
- Finisher (hole-puncher, stapler and stacker)

Built-in Web Browser

The CL30 has a built-in web browser which allows user to check the status of the printer and perform other administrative functions over the internet, including:

- View status of the printer
- Change network configuration
- Configure alerts: the printer can send an email to the administrator (or to you) when it needs consumables or service
- Change Printer menu configuration, such as paper size, type, colour settings etc.
- View usage rates or current consumables status

E-mail Alerts

Up to seven e-mail addresses can be programmed into the CL30. The appropriate people can then be notified, in advance, before the printer stops printing.

†Page sizes over 304 x 901mm (12" x 18") can only be printed using the multipurpose tray.



Call XANTÉ Europe today for more information
+31-26-319-3210 • Fax +31-26-319-3211
 europesales@xante.com • europesupplies@xante.com
www.xante.com

© 2003 XANTÉ CORPORATION. XANTÉ is a trademark or registered trademark of XANTÉ CORPORATION. Adobe, PostScript, PostScript 3 and the Clearly Adobe Imaging and PostScript logos are trademarks or registered trademarks of Adobe Systems Incorporated. Other brands and product names are trademarks or registered trademarks of their respective holders. XANTÉ CORPORATION: Post Office Box 16526, Mobile, AL 36616-0526, USA, Phone: 251-473-6502, Fax: 251-473-6503, www.xante.com

XANTÉ **CL³⁰**

FEATURES

- 30 Pages-Per-Minute of Full Color
- High Performance, High Volume
- 1200 x 1200 DPI
- Print Spooling and Job Storage
- Automatic Color Recalibration
- Duplexing Capabilities
- Color Management
- Adobe® PostScript® 3™



XANTÉ

CLEARLY™
Adobe

IMAGING